



# PRODUCT BULLETIN

NUMBER: R0005

DATE: 27 Oct 2023



R25PSV model shown

## New 3PH Stump Grinders

Adding to its professional line of land management tools, Reist introduces its Dominator series of Stump Grinders. Designed for 3PH applications, the initial offering will include two models.

A uniquely designed rotor sheds unnecessary weight increasing rotor acceleration helping to maximize available PTO horsepower. Utilizing carbide Wearsharp® carbide teeth, with their triangular shaped base allows them to be indexed 3 times tripling the already long-lasting wear life of the carbide. When combined with our proprietary rotor design, the result is increased acceleration and cutting performance.

Model	Description	List Price
R25PD	3PH, PTO driven, Direct Drive	\$ 3,820.00
R25PS	3PH, PTO driven, Hydraulic Swing <i>(no valve requires 2 sets of remotes)</i>	\$ 7,960.00
R25PSV	3PH, PTO driven, Hydraulic Swing <i>(optional valve, requires only 1 set of remotes)</i>	\$ 9,075.00

Toll Free: (877) 467-3478

Tel: (519) 669-1501

[www.reistindustries.com](http://www.reistindustries.com)

100 Union Street, Elmira Ontario N3B 3L7



R25PD model shown



R25PSV model shown

### R25PD Direct Drive Features

- Quick hitch compatible
- Category I compatible
- Slip clutch protection
- 700 Series WearSharp© carbide teeth
- One way cutting
- Park stand

### R25PS Hydraulic Swing Features

- Quick hitch compatible
- Category I & II compatible
- Slip clutch protection
- 700 Series WearSharp© carbide teeth
- Greaseable pins
- One way cutting
- Extended frame for stable footing
- Durable HDPE deflector to help contain debris
- Depth/lift gauge

Part Number	Description	List Price
STGV	R25PS Valve option includes hoses (no cylinders)	\$ 1,620.00
700-WS	WearSharp© Tooth	\$ 26.00
500-NUT	Nut for tooth above	\$ 1.75
700-SPACER	Spacer	\$ 2.00

Technical Specifications	R25PD	R25PS
Recommended HP	20-45 HP	25-80 HP
PTO Speed (input speed)	540 RPM	540 RPM
Rotor Size	25"	25"
Tooth Construction (indexable 3x)	Carbide bolt into pocket	Carbide bolt into pocket
Number of Teeth	18	18
Cutting Wheel Speed	540 RPM	1026 RPM
Cutting Height (above grade)	10"	20"
Cutting Height (below grade)	7"	6"
Cutting Depth (per pass)	2.25"	2.25"
Cutting Width (per pass)	22"	22"
Swing Arc	0°	55°
Protection	Slip clutch	Slip clutch
Hitch	Cat I	Cat I & II
Quick Hitch Compatible	Yes	Yes
Hydraulic Remotes Required	No	1* or 2

*\*Requires optional valve to control both lift and swing functions.*

Shipping Specifications	R25PD	R25PS
Weight	460 Lbs.	950 Lbs.
Length	36"	42"
Width	42"	72"